

"Express Mail" mailing label number: EV340866180US

Date of Deposit: March 31, 2004

Attorney Docket No. 8627-372

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
APPLICATION FOR UNITED STATES LETTERS PATENT

INVENTORS:

Roy K. Greenberg, Krasnodar
Ivancev, and Ram H. Paul, Jr.

TITLE:

Medical Grasping Device

ATTORNEYS:

John M. Card, Reg. No. 48,423
BRINKS HOFER GILSON & LIONE
P.O. BOX 10395
CHICAGO, ILLINOIS 60610
(734) 302-6000

RELATED APPLICATIONS

[0001] This application is a continuation-in-part of U.S. Patent Application No. 10/003,011, filed November 1, 2001, which claims the benefit of U.S. Provisional Application No. 60/245,811, filed November 3, 2000.

[0002] The contents of the above applications are incorporated herein in their entirety.

TECHNICAL FIELD

[0003] This invention is related to medical devices and in particular to a medical grasping device.

BACKGROUND

[0004] There is a current trend in medicine to minimize surgical and interventional procedures, concomitant with the development of minimally invasive tools to access, visualize, infuse, treat, medicate, sample, and interact with internal structures of the body. Occasionally, devices such as catheters, balloons or wires are inadvertently severed in a blood vessel, cavity or organ. Depending on its location, the severed device or fragment must be retrieved. Frequently, a surgical approach is dangerous and costly. In many cases, access has already been established to the severed device, fragment, or foreign body in question, and it is just a matter of locating and removing the foreign body without doing harm to surrounding tissue or forcing it further out of reach.

[0005] Certain medical devices are known that are utilized in the ducts and vessels of a human or veterinary patient for retrieval of bodies from the patient. For

example, retrieval devices are known for removing calculi such as kidney stones or gallstones from a patient, where the retrieval device is delivered to the target site via the urethra or biliary duct, respectively. The device's distal tip is adapted to deploy at the site to form a basket shape to trap the calculi after which the basket is collapsed to grasp the calculi. Both the device and the grasped calculi are then withdrawn from the patient.

[0006] One such stone retrieval device is disclosed in U.S. Pat. No. 5,989,266, in which several loops of wire are caused to emerge from the distal end of a sheath that has previously been delivered through the renal or biliary system of a patient to the site of the stone. The stone becomes trapped within the loops, after which the loops are pulled proximally mostly into the sheath, grasping the stone firmly, after which the sheath, loops and stone are withdrawn from the patient. The loops are disclosed to be made from a superelastic alloy such as nitinol to automatically form the loops when caused to emerge from the sheath's distal tip. Other similar stone retrieval devices are disclosed in U.S. Pat. Nos. 5,057,114; 5,064,428; 5,133,733 and 5,484,384.

[0007] However, use of such devices is not satisfactory for grasping such an object within the vascular system of a patient for repositioning of that object, or for removal of objects from within the vascular system of a patient. For example, in certain situations it is desired to reposition a stent or stent graft within the vasculature, or to retrieve or reposition a malpositioned or misplaced embolization coil. And during delivery and deployment of a bifurcated stent graft at the site of an abdominal aortic aneurysm when surgical access has been obtained through the femoral arteries on both sides of the groin, it is desirable to grasp the distal tip of a

guide wire extending into the aneurysm from the contralateral iliac artery, to be pulled into the ipsilateral iliac artery at the vessel's aorto-iliac bifurcation, for eventual placement of the contralateral leg extension of the stent graft.

[0008] For vascular use, another known device is a suture loop on a catheter distal tip. Yet another is a guide wire that has been doubled over and extended through a catheter so that its distal end forms into a loop that extends axially from the catheter's distal end to be utilized as a retriever when it is pulled proximally to capture an object and hold it against the catheter distal end for withdrawal, sold as the Curry Intravascular Retriever Set by Cook, Incorporated, Bloomington, Ind. A version of the stone basket device, having helical loops, has been utilized for intravascular retrieval, the Dotter Intravascular Retriever Set also sold by Cook, Incorporated.

[0009] In U.S. Pat. No. 5,171,233 is disclosed a snare-type probe for intravascular use. After a catheter is inserted into the patient's vascular system to the site of the foreign object, an elongate member having a loop-shaped distal segment is inserted into the proximal end of the catheter's lumen until the loop-shaped distal segment emerges from the catheter's distal tip at the site. Then the loop-shaped segment extends at an angle to the adjacent portion of the member and opens into a loop. Once a free end of the foreign object is snared within the loop-shaped distal segment as determined by fluoroscopic equipment, the loop-shaped distal segment is pulled proximally into the catheter distal end, collapsing about the ensnared foreign body fragment and holding the foreign body at the distal tip of the catheter during withdrawal. The elongate member is preferably disposed within an outer sheath and is disclosed to be one wire, or two gripped-together wires, of a

shape memory material such as a superelastic nitinol alloy, with a single preformed loop shape at the distal segment defined by two wire portions. The use of nitinol enables the wire segments defining the distal segment to be straightened and collapsed upon one another into an elastically deformed configuration to pass through the lumen of the catheter and yet automatically open into a loop and extend at a substantial angle upon emerging from the catheter distal tip. One characteristic of this design is that during retraction after grasping, the loop quickly changes, or "flips," between the angled orientation and a generally axial one, and this results in less assured control over the item during grasping, and commonly will result in escape of the item thus requiring redeployment of the loop for another grasping attempt.

[0010] It is desired to provide a medical grasping device for grasping and repositioning an object within the vascular system of a patient, such as a stent or stent graft or embolization coil or such as the distal tip of a catheter or a guide wire; or to grasp a stent or embolization coil, or a fragment from a catheter or guide wire or a pacemaker lead, for its removal from the patient.

[0011] It is also desired to provide a low profile, medical grasping device that is conformable to the vascular anatomy while generating a substantial tensile force.

[0012] It is further desired to provide such a device that is trackable through the vascular system over a guide wire already in situ.

[0013] It is yet further desired to provide such a device that is atraumatic to the patient.

[0014] It is yet further desired to reduce physician fatigue during the operation of the device.

SUMMARY OF THE INVENTION

[0015] The present invention provides a medical grasping device including an elongate control member, an outer sheath, and an actuation section. The elongate control member includes an atraumatic distal tip section, a proximal end portion, and a grasping portion positioned between the proximal end portion and the distal tip section. The outer sheath includes a distal end and a proximal end, and has a passageway that extends between the distal and proximal ends. The elongate control member is slidable within the passageway and its proximal end portion is connected to the actuation section. The actuation section is operated to move the grasping portion in and out of the distal end of the outer sheath and includes a retraction mechanism that biases the actuation section and hence the grasping portion towards a retracted state.

[0016] With the use of the retraction mechanism, the physician has to exert a force to the actuation section only when an item is to be grasped by the grasping portion. As such, the retraction mechanism can reduce physician fatigue. Moreover, the retraction mechanism may act as a resistive feed-back force so that the physician can precisely control the operation of the grasping portion.

[0017] Other advantages and features will be apparent from the detailed description and from the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] Embodiments of the present invention will now be disclosed by way of example with reference to the accompanying drawings, in which:

[0019] FIG. 1 is an elevation view of the grasping device of the present invention;

[0020] FIG. 2 is an enlarged partial section view of the device of FIG. 1;

[0021] FIG. 3 is an exploded elevation view showing the components of the grasping device of FIGS. 1 and 2;

[0022] FIG. 4 is an enlarged view of the grasping portion of the device;

[0023] FIG. 5 is an isometric view illustrating one of the wire segments defining one of the loops;

[0024] FIGS. 6 to 9 are enlarged cross-sectional views of the grasping portion and distal tip of the device prior to deployment, during deployment, fully deployed, and partially retracted after grasping a target catheter end, respectively;

[0025] FIG. 10 is an enlarged end view of the distal end portion of the device illustrating the grasping portion of the device fully deployed;

[0026] FIG. 11 is an enlarged end view of an alternate embodiment of the grasping portion of the present invention;

[0027] FIG. 12 is an enlarged view of the actuation section of the proximal controls;

[0028] FIG. 13A is an elevation view of an alternative embodiment of a grasping device; and

[0029] FIG. 13B is an exploded view of the grasping device of FIG. 13A.

DETAILED DESCRIPTION

[0030] With regard to FIGS. 1 to 3, grasping device 10 of the present invention includes an outer sheath 12 extending from a distal end portion 14 to a proximal end 16. Secured to the proximal end 16 is proximal control assembly 22 including a handle 20 that is affixed to the outer sheath 12. Proximal control assembly 22 also includes an actuation section 24 that is movably affixed to the handle 20, and that is in operative relationship with an elongate control member 50 that is disposed within outer sheath 12 and extends along passageway 18 completely therethrough to a distal end portion 52 that is adjacent to distal end portion 14 of outer sheath 12. Outer sheath 12 also includes adjacent to its distal end 30 a radiopaque marker band 32. Distal end portion 52 of control member 50 concludes in a distal tip section 54, and spaced proximally from the proximal end 56 of distal tip section 54 is the grasping portion 70 of the present invention.

[0031] Elongate control member 50 is preferably a cannula or tube having a guide wire lumen 58 extending completely therethrough, for receipt therethrough of a guide wire 28. Guide wire 28 need not be part of the grasping device 10 of the present invention, but the present invention is particularly designed to be used therewith and would be of the type conventionally in use for various intravascular procedures. Elongate control member 50 has an outer diameter that is less than the inner diameter of passageway 18 to enable relative axial movement within the outer sheath 12 when actuated. Elongate control member 50 has a distal tip section 54 that is blunt and rounded to be atraumatic to the patient, preferably tapered to its rounded tip from the outer surface of outer sheath 12 at distal sheath end 30 to provide a smooth transition between the outer sheath and the guide wire 28. The

atraumatic tip protects the vessel wall and reduces the chance that the distal tip of the grasper device will shear off any atheromatous plaque that it encounters while tracking through the vascular vessel. At proximal end portion 60 of elongate control member 50 is a connection 62 to actuation section 24.

[0032] A side flushport fitting 96 with a T-shaped lumen therein is affixed to the front end of handle 20 such as by snap coupling 98 and secures therewithin a seal 36 surrounding control member 50, such as a flat flexible sealing washer, and holds it tightly against the front end of handle 20. Seal 36 defines hemostatic sealing of passageway 18 around control member 50. A cap 38 attaches outer sheath 12 to a threaded forward portion of adapter fitting 34. Cap 48 keeps the lumen of flushport fitting 96 sealed when not connected to a fluid source. Preferably, outer sheath 12 includes an enlarged or flared proximal end 40 on proximal end 16 that is tightly gripped by cap 38, and enlarged proximal end 40 may be complementary to a conical forward end of threaded forward portion of fitting 34. Handle 20 preferably includes a thumb ring 42. Seen extending rearwardly and at a gradual angle laterally from handle 20 is tubing 44 that is affixed to the rearward end of control member 50 and having a passageway along which guide wire 28 extends, with tubing 44 including thereon a Touhy-Borst adaptor 46, for hemostatic sealing around the guide wire proximally of control member 50.

[0033] Referring now to FIGS. 4 and 5, the grasping portion 70 is preferably defined by wire segments 72 that define loops 74. Wire segments 72 are preferably fabricated from a superelastic material such as nitinol. Proximal ends 76 of the wire segments may be affixed to the control member at affixation joints 78, such as by low-temperature soldering as in U.S. Pat. No. 5,354,623, or, less preferably, welding

to a stainless steel band 80 that is affixed to distal end portion 52 of control member 50 such as by crimping or bonding.

[0034] As depicted in FIG. 8, each loop 74 of grasping portion 70 includes arcuate outer sections 82 that extend to be adjacent or in abutment with wall 84 of vessel 86. Each loop 74 also includes arcuate side sections 88 that extend toward the axial center of the grasping portion 70 and then curve gradually toward the distal end of the control member and affixation joints 78. Preferably, wire segment proximal ends 76 coextend coaxially at least distally along the outer surface of the control member 50 from the affixation joints 78, and continuously and gradually extend to those portions that will define loops 74 upon emerging from outer sheath 12 upon actuation. Also, preferably, proximal ends 76 that are affixed to the control member are within the cold-worked bend 74A of the nitinol wire segment (FIG. 5), since this assures the gradual curving of that portion of loop 74 adjacent the axis as it emerges from the distal end of the outer sheath. As depicted in FIG. 5, fabrication of the affixation joints may be most easily accomplished if the wire segment 72 initially includes unbent straight segments 76A extending from ends 78A of loop 74A for ease in controlled forming, handling and positioning of the wire segment, after which at least most of segments 76A are removed.

[0035] Soldering of nitinol to stainless steel is disclosed in U.S. Pat. No. 5,354,623. Wire segment proximal ends 76 may also be secured by bonding or another form of affixation directly to control member 50 or to another intermediate member similar to band 80. Forming of the wire loops from nitinol may be attained by stress-inducing the wires into that shape during heat treatment or annealing of the grasping portion in the loop shape to create stress-induced martensite (SIM) at

the loops as disclosed in U.S. Pat. No. 5,597,378 while the remainder of the wires has an austenitic state. The preforming of the loops may also be attained by cold-working the loops as is disclosed in PCT Publication WO 00/33909, by over-bending a wire in the austenitic state about a fixture. Cold-working permanently locks a portion of the crystalline structure of the bending zone into at least a partial martensitic condition while the unstressed portions of the wire remain in the austenitic state.

[0036] Referring now to FIGS. 6 to 9, grasping portion 70 is shown in more particularity. In FIG. 6, grasping portion 70 is seen in its recessed state within distal end portion 14 of outer sheath 12, as atraumatic tip section 54 extends beyond distal sheath end 30 from control member 50. Wire segments 72 are held entirely within outer sheath 12, along distal end portion 52 of control member 50 distally of affixation joints 78 and extending axially from proximal wire portions 76. Affixation joints 78 are disposed preferably within stainless steel band 80. Loops of the wire segments 72 are seen in a constrained condition 74B along the control member just proximally of proximal end 56 of atraumatic distal tip section 54. Outer sheath 12 preferably includes a radiopaque marker band 32 around its outer surface at distal end portion 14 a small distance from sheath end 30.

[0037] FIG. 7 illustrates partial deployment of grasping portion 70. It is clearly seen that wire segments 72 curve gradually and continuously from control member 50 forwardly and eventually radially outwardly to outer sections 82 beyond sheath end 30 during deployment as the loops 74 begin to open, and exhibit a corollary curving during retraction into outer sheath 12.

[0038] In FIG. 8 is seen grasping portion 70 fully deployed within vessel 86, with outer sections 82 of loops 74 abutting vessel wall 84. Guide wire 28 is seen extending forwardly from atraumatic distal tip section 54. Proximal wire segment sections 76 are seen to maintain a continuous, gradual curvature as they exit from distal end 30 of outer sheath 12 to form loops 74.

[0039] A target object T has been snared by grasping portion 70 in FIG. 9, and grasping portion 70 has been mostly retracted into outer sheath 12 so that the target object is held firmly against outer sheath 12, and nearby portions of atraumatic distal tip section 54 and possibly distal end portion 52 of control member 50 adjacent to tip section 54. In this instance, the target object is a catheter whose end portion is to be repositioned.

[0040] Loops 74 are shown in FIG. 10 as substantially circular, extending to arcuate outer sections 82 with arcuate side sections 88 that extend toward the center of the grasping portion 70 and then curve toward the distal end of the control member and affixation joints 78. Side sections 88 of each loop 74 are seen to overlap to some extent with side sections 88 of adjacent loops 74. Altogether, when arcuate outer sections 82 abut the vessel wall 84 of vessel 86, the loops 74 are seen to traverse substantially the entire cross-section of the vessel.

[0041] In FIG. 11 is shown an alternate embodiment of grasping portion 70'. Grasping portion 70' comprises four pie-shaped loops 74', each defined by wire segments 72' that preferably are superelastic material such as nitinol. Each pie-shaped loop 74' includes an outer section 82' that is arcuate for abutment against the vessel wall 84 of vessel 86 and having a radius about equal to the radius of the vessel at the target site, and opposed radial side sections 88' converging to the

center of the grasping portion. It can be seen the entire cross-section of the vessel 86 is traversed by the grasping portion when deployed. As with grasping portion 70 of FIG. 10, side sections 88' may overlap those of adjacent loops 74'.

[0042] With reference now to FIGS. 2, 3 and 12, proximal control assembly 22 is shown in greater particularity and includes an ergonomic easily grippable spool-shaped slide member 100 that is reciprocally movable along handle 20 to in turn actuate control member 50 to move with respect to outer sheath 12 attached to handle 20. Slide member 100 is fastened such as by set screws 102 to a connecting block 104 that is affixed to control member 50 extending into a central passageway 106 of handle 20 through cap 38, fitting 34 and flushport 96. Connecting block 104 is shown to be disposed within a slot 108 of handle 20. Slot 108 thus defines the limits of movement of connecting block 104 and thus of control member 50. Connecting block 104 includes an axial opening therethrough and is affixed to the proximal end of control member 50 such as by being disposed rearwardly of an annular forward stop collar 110, after which a barbed fitting 112 is placed onto the projecting rearward end 114 of control member 50 rearwardly of the connecting block 104 to form the rearward stop. Barbed fitting 112 also sealingly secures tubing 44 to rearward end 114 of control member 50. Preferably, the rearward end of slot 108 is scalloped to define a controlled shallow exit for tubing 44, through which will extend guide wire 28.

[0043] Actuation section 24 may preferably include a spring-loaded retraction section that upon manual release thereof retracts the grasping portion 70,70' into the distal end portion 14 of the outer sheath 12, and simultaneously captures the target

body T within one of the loops 74,74' so that it is held against distal sheath end 30 and distal end portion 52 of control member 50 (see FIG. 9).

[0044] For example, an alternative embodiment shown in FIGs. 13A and 13B as a grasping device 200 includes an actuation section 24 with a retraction mechanism 202. The retraction mechanism includes a spring 204 mounted about the handle 20 and partially about the snap coupling 98. The spring 204 extends between a face 206 of the slide member 100 and a flange 208 attached to the snap coupling 98. The flange 208 may be a separate piece mounted about the snap coupling 98 or it may be an integrally molded with the snap coupling 98 such that the flange 208 is an extension of the snap coupling 98. As illustrated, the spring 204 is a helical spring, which can be made from, for example, stainless steel or from any other suitable material. However, the spring 204 need not be limited to the type of spring show in FIGs. 13A and 13B. The spring 204 can be any suitable mechanism that when released from a compressed state returns to an elongated state.

[0045] The spring 204 biases the actuation section 24 toward the rear or proximal end of the handle 20. Hence, the spring 204 biases the grasping portion 70 in a retracted state within the outer sheath 12. Thus, the physician can guide the distal end of the sheath at a site of interest within the patient's body before actuating the grasping device 200. Once the sheath 12 is located at the site of interest, the physician can push the actuation section 24 forward to push the grasping portion 70 out of the distal end of the sheath 12 and then manipulate the grasping device 200 so that one of the loops 74 captures the item to be retrieved from the patient's body. Once the item is within one of the loops 74, the physician can slowly or quickly reduce the resistive force imparted to the spring 204 through the slide member 100

to let the spring force of the spring 204 push the actuation section 24 toward the rear of the grasping device 200. By doing so, the actuation section 24 draws the grasping portion 70 back into the sheath 12 until the item of interest is securely grasped between one of the loops 74 and the distal tip section 54.

[0046] Since the physician has to exert a force to the actuation section 24 only when an item is to be grasped by the grasping portion 70, the retraction mechanism 202 can reduce physician fatigue. Moreover, the retraction system acts as a resistive feed-back force so that the physician can precisely control the operation of the grasping portion 70.

[0047] The retraction section may further include a lock (not shown) that enables the grasping portion to automatically hold the grasped object T with a preselected limited grasping force during movement of the grasping device by the practitioner; such lock may be of the ratchet kind that may be manually set by the practitioner after sufficient grasping has been attained for the immediate purpose. The limited amount of force thus would protect the grasped object from damage especially were it to be of continued value in treating the patient after repositioning thereof.

[0048] Outer sheath 12 is very similar to a guiding catheter in structure and function, and may be formed for example with an inner liner of polytetrafluoroethylene and an outer jacket of a polyamide such as nylon, and may be reinforced such as by a spiral-wound flat stainless steel wire coil embedded between an inner nylon liner and an outer jacket, all in a manner disclosed in greater detail in U.S. Pat. No. 5,769,830 in order to be kink-resistant. The outer surface of the outer jacket may be coated for example with a lubricious material such as

AQ.TM. Hydrophilic Coating. The control member 50 may be formed for example of thermoplastic material such as polyethylene terephthalate. The distal tip section 54 may be a separate member of a softer, lower durometer material of conventional composition. Lumen 58 preferably has a diameter of up to 0.040 in to allow free passage over guide wires that would have diameters of up to 0.038 in as is common.

[0049] Elongate control member 50 may be fabricated by braiding of the material in a manner that imparts the ability of the control member to be torqued, that is, to be rotated by the proximal control assembly 22 for adjusting the grasping portion about the axis, if desired. Such braiding should be from such materials and in such a manner that does not result in noticeable elongation during retraction of the grasping portion, or withdrawal of the device during total removal of the target object.

[0050] The device includes a flushport fitting to allow flushing with sterile saline solution between the elongate control member and the outer sheath to eliminate air, while the device is outside of the patient. An air seal can be utilized near the distal end of the sheath.

[0051] The grasping device of the present invention can be useful in any multiple access vascular procedure for adjusting the final position of a medical device, such as through the iliac or subclavian arteries. The invention can additionally be useful with the liver or kidney or other nonvascular procedure, especially where access to the site involves a tortuous path, since the grasping device is flexible and is adapted to follow a guide wire.

[0052] The above and other implementations are within the scope of the following claims.